



PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 47716

1. OWNER EDWIN RODRIGUEZ ADDRESS AT WELL LOCATION 15700 15574 Red Rock Road  
 MAILING ADDRESS 15064 Red Rock Road Reno, Nevada 89506  
 2. LOCATION NE 1/4 NE 1/4 Sec. 12 T. 22N N/S R. 18 E Washoe County Washoe  
 PERMIT NO. 079-381-24 Parcel No. Red Rock Estates #83 parcel A Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Decomposed granite		0	2	2
Weathered granite				
rusty brown		2	15	13
Brown clay streaks		15	18	3
Weathered granite		18	36	18
Clay streaks		36	37	1
Weathered rusty brown granite		37	92	55
Soft zone (NO WATER)		92	93	1
Weathered granite		93	129	36
Gray granite		129	289	160
Weathered granite (soft)		289	318	29
Gray granite		318	437	119
Weathered granite with clay streaks		437	455	18
Gray granite		455	485	30
Reddish brown granite		485	530	45
Gray granite		530	598	68
Fracture	X	598	605	7
Gray granite		605	645	40
Fracture	X	645	646	1
Gray granite		646	672	26

8. WELL CONSTRUCTION  
 Depth Drilled 672 Feet Depth Cased 672 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 0 Feet To 50 Feet  
10 Inches  
 From 50 Feet To 672 Feet  
8 5/8 Inches  
 From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	672

Perforations:  
 Type perforation factory sawed slot  
 Size perforation 3/32 x 3 x 5 around  
 From 600 feet to 620 feet  
 From 625 feet to 665 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Neat Cement  
 Cement Grout  
 Concrete Grout  
 Depth of Seal 50 feet  
 Placement Method:  Pumped  Poured  
 Gravel Packed:  Yes  No  
 From 50 feet to 672 feet

9. WATER LEVEL  
 Static water level 555 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. 30 P.S.I.  
 Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WAYNE DRILLING, INC. Contractor  
 Address P.O. BOX 12370 Contractor  
RENO, NEVADA 89510  
 Nevada contractor's license number 0022549 issued by the State Contractor's Board  
 Nevada driller's license number issued by the Division of Water Resources 923  
 Signed [Signature] By driller performing actual drilling on site or contractor  
 Date January 22, 2002

Date started January 18, 2002, 19\_\_\_\_  
 Date completed January 21, 2002, 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>30</u>		