WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 86316
Permit No.
Basin 69

NOTICE OF INTENT NO. 48286

1. OWNER Max & Teresa Willis
MAILING ADDRESS P.O. Box 89 Paradise Nv 89426
ADDRESS AT WELL LOCATION 110 Main Street Paradise Nv 89426

2. LOCATION SW ¼ NW ¼ Sec. 25 T. 42 N/S R. 39 E. Humboldt County
PERMIT NO. Domestic (Issued by Water Resources) 04-531-30 (Parcel No.) Burhans (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| top soil | | 0 | 10 | 10 |
| sand | | 10 | 50 | 40 |
| gravel 3/8 | yes | 50 | 70 | 20 |
| clay | | 70 | 100 | 30 |
| sand | | 100 | 140 | 40 |
| clay | | 140 | 160 | 20 |
| sand fine | yes | 160 | 200 | 40 |
| clay | | 200 | 250 | 50 |
| gravel / sand | yes | 250 | 300 | 50 |

Date started Feb 26 2002
Date completed March 1 2002

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 150 | | 4 |

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 298 Feet

HOLE DIAMETER (BIT SIZE)

| Inches | From (Feet) | To (Feet) |
|---|---|---|
| 12 5/8 | 0 | 300 |
| | | |
| | | |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 8 | 12 | 1.88 | +1 | 298 |
| | | | | |
| | | | | |

Perforations:
Type perforation Factory cut
Size perforation 3/32 X 4
From 260 feet to 300 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 100
Placement Method: ☒ Pumped 4 TO 40 ☐ Poured 40 TO 100
Abantowite
Gravel Packed: ☒ Yes ☐ No
From 100 feet to 300 feet

Seal Type:
☒ Neat Cement
☐ Cement Grout
☐ Concrete Grout

9. WATER LEVEL
Static water level 20 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature Cool °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Fred Anderson Drilling (Contractor)
Address 10760 Grass Valley Rd (Contractor)
Winnemucca, Nv 89445
Nevada contractor's license number issued by the State Contractor's Board 021467
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 01375
Signed (By driller performing actual drilling on site or contractor)
Date March 5-02

(Rev: 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627