WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
Monitor Well #CI-3157
WELL DRILLER'S REPORT
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 86332
Permit No.
Basin 72

NOTICE OF INTENT NO. 43489

1. OWNER FLORIDA CANYON MINING, INC.
MAILING ADDRESS P.O. BOX 330
IMLAY, NV 89418

ADDRESS AT WELL LOCATION HISTORIC STANDARD MINE AREA

2. LOCATION NE ¼ NE ¼ Sec. 35 T. 31 N N/S R. 33 E PERSHING County
PERMIT NO. M/O 1229 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
XX New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial XX Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary XX RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SILICIFIED LIMESTONE		0	125	125
GRAY LIMESTONE		125	140	15
RED SILTSTONE		140	165	25
GRAY LIMESTONE		165	180	15
BLACK SILTSTONE		180	190	10
GRAY CLAY		190	195	5
GRAY TO RED LIMESTONE		195	210	15
GREEN SILTSTONE		210	260	50
GRAY TO BLACK LIMESTONE		260	410	150
HOLE DRY - NO WATER				

Date started DECEMBER 19, 2001, 19
Date completed DECEMBER 20, 2001, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 410 Feet Depth Cased 235 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
5 1/8 Inches		0 Feet	410 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	PVC	SCH 80	+2	235

Perforations:
Type perforation MILL SLOT PVC
Size perforation .020
From 50 feet to 235 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: XX Yes ☐ No
Depth of Seal 65
Placement Method: XX Pumped ☐ Poured

Seal Type: XX Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: XX Yes ☐ No
From 65 feet to 235 feet

9. WATER LEVEL
Static water level N/A DRY feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name DELONG CONSTRUCTION & DRILLING (Contractor)
Address P.O. BOX 907 (Contractor)
WINNEMUCCA, NV 89446

Nevada contractor's license number issued by the State Contractor's Board 0002120C

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 01375

Signed [signature] (By driller performing actual drilling on site or contractor)
Date JAN 14 - 2002

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627