WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 86671
Permit No.
Basin 212

NOTICE OF INTENT NO. 23364

1. OWNER CLARK COUNTY SANITATION DISTRICT
MAILING ADDRESS
ADDRESS AT WELL LOCATION PROPOSED CROSSING OF LAS VEGAS WASH AND EFFLUENT INTERCEPTOR

2. LOCATION NW ¼ NE ¼ Sec. 15 T. 21 N/S R. 62 E. CLARK County
PERMIT NO. (Issued by Water Resources) 161-15-501-001 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SILTY CLAY		0	5	5
SILTY CLAY WITH SAND		5	17	12
SILTY CLAY WITH GRAVEL		17	20	3
CLAYEY SAND WITH GRAVEL		20	25	5
CLAYEY SAND WITH SILT		25	32	7
SILTY SAND WITH CLAY		32	42	10
SILTY SAND WITH GRAVEL		42	53	11
SILTY SAND WITH CLAY		53	62	9
CLAY WITH SAND		62	67	5
CLAY WITH SILT		67	75	8
SILTY CLAY WITH GRAVEL		75	80	5
SAND WITH GRAVEL		80	85	5
CLAY WITH SILT		85	90	5
CLAY WITH SAND		90	100	10

Date started 6/11/02, 19
Date completed 6/11/02, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 100 Feet Depth Cased 100 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
4.75 Inches		0 Feet	100 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"			0	100

Perforations:
Type perforation FACTORY SLOT
Size perforation 0.020 INCH
From 90 feet to 100 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 78.2
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 78.2 feet to 100 feet

9. WATER LEVEL
Static water level 7.41 feet below land surface
Artesian flow NO G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name CONVERSE CONSULTANTS (Contractor)
Address 731 PILOT ROAD STE H (Contractor)
LAS VEGAS, NV 89119
Nevada contractor's license number issued by the State Contractor's Board 48947
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1589
Signed (By driller performing actual drilling on site or contractor)
Date

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627