

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO 22799

1. OWNER Am Pac Development Company ADDRESS AT WELL LOCATION \_\_\_\_\_  
 MAILING ADDRESS 3770 Howard Hughes Parkway Suite 300 Las Vegas, NV 89109 SWC Gibbon Rd + American Pacific Dr  
 2. LOCATION NE  $\frac{1}{4}$  NE  $\frac{1}{4}$  Sec. 15 T. 22 N/S R. 62 E CLARK County  
 PERMIT NO. \_\_\_\_\_ Parcel No. 178-15-511-021 Subdivision Name \_\_\_\_\_  
 Issued by Water Resources \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. IW-1FEU1 LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
<u>Pale Brown Silty Sand with gravel and some cobbles</u>		<u>0</u>	<u>14.0</u>	<u>14.0</u>
<u>Dense cemented gravel</u>		<u>14.0</u>	<u>30.0</u>	<u>16.0</u>
<u>Brown silty, Clayey Sand very dense</u>	<u>25.0</u>	<u>30.0</u>	<u>40.0</u>	<u>10.0</u>
<u>Brown silty Clay w sand, with gravel</u>	<u>40.0</u>	<u>40.0</u>	<u>130.0</u>	<u>110.0</u>
<u>Brown poorly graded sand with silty clay</u>	<u>130.0</u>	<u>130.0</u>	<u>160.0</u>	<u>30.0</u>
<u>Brown silty sand w/ gravel, weakly cemented</u>	<u>190.0</u>	<u>160</u>	<u>195.0</u>	<u>35.0</u>

8. WELL CONSTRUCTION  
 Depth Drilled 0 Feet Depth Cased 180 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 0 To 195.0  
9 7/8 Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 CASING SCHEDULE  

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>4"</u>	<u>SCH 40</u>		<u>72</u>	<u>160</u>

 Perforations:  
 Type perforation MACHINE SLOTTED  
 Size perforation 1.020  
 From 160 feet to 180 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 152.0  
 Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 180.0 feet to 152.0 feet  
 9. WATER LEVEL  
 Static water level 15 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature Coal °F Quality Rocket Fuel

Date started 3/4 2002, 19  
 Date completed 3/11 2002, 19

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name EAGLE DRILLING SERVICES LLC  
 Address 7150 Placid Rd LAS VEGAS NV, 89119  
 Nevada contractor's license number 51766 issued by the State Contractor's Board.  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2193  
 Signed Victor Lim  
 by driller performing actual drilling on site or contractor  
 Date 05/16/02