87627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 87627
Permit No.
Basin 212

NOTICE OF INTENT NO. 24128

1. OWNER Catharine E. Chiazzese
MAILING ADDRESS
ADDRESS AT WELL LOCATION Vacant Lee Canyon Rd.

2. LOCATION SE ¼ NW ¼ Sec. 6 T. 19S N/S R. 59 E CLARK County
PERMIT NO. (Issued by Water Resources) 126-06-201-005 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Gravel		0	325	
Red Sandstone		325	340	
Red Shale		340	450	
Red Sandstone		450	505	
Red Shale & Water	xx	505	530	
Red Sandstone		530	600	
Red Shale & Water	xx	600	650	

RECEIVED
FEB 04 2003
LAS VEGAS OFFICE

Date started 12/12/~~03~~ 02, 19
Date completed 1/12/03, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 650 Feet Depth Cased 650 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 1/4 Inches		0 Feet	50 Feet
9 7/8 Inches		50 Feet	650 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	SCH 80	PVC	5	50
8 5/8	16.94	.188	0	5
6 1/2"	PVC SDR		+1	650

Perforations:
Type perforation Factory
Size perforation .032 Sieve Type
From 600 feet to 640 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout
Gravel Packed: [ ] Yes [X] No
From feet to feet

9. WATER LEVEL
Static water level 340 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Vernon H. Dimick (Contractor)
Address 5360 N. Bonita Vista (Contractor)
Las Vegas, Nev. 89149
Nevada contractor's license number issued by the State Contractor's Board 10062
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 552
Signed V H Dimick (By driller performing actual drilling on site or contractor)
Date 1-15-03

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627