

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
 Log No. 87844  
 Permit No. 61248T  
 Basin 061

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in  
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 43268

1. OWNER Barrick Goldstrike Mines PPW-78 ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV.  
 MAILING ADDRESS P.O. Box 29 Elko, NV 89803

2. LOCATION NE 1/4 NE 1/4 Sec. 30 T 36N N/S R 50E E Eureka County  
 PERMIT NO. 61248-T Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<b>Top 192' of well has been mined off. The original construction data are given at right. However, seal and gravel pack data reflect current condition of the well.</b>				
<b>Well was abandoned by pumping abantonite via tremie from T.D. to 444', poured hole plug to 10', and capped with 10' of neat cement.</b>				
<b>Quantities Used:</b>				
<b>Cement: 4.7 cu.ft</b>				
<b>Hole plug: 109 cu.ft.</b>				
<b>Abantonite: 175 cu.ft.</b>				

Date started 4/24/2002, 19  
 Date completed 4/25/2002, 19

7. WELL TEST DATA

TEST METHOD:	TEST METHOD:		Time (Hours)
	G.P.M.	Draw Down (Feet Below Static)	

8. WELL CONSTRUCTION

Depth Drilled 1015 Feet Depth Cased 1008.67 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
<u>19</u> Inches	<u>0</u> Feet	<u>30</u> Feet
<u>13</u> Inches	<u>30</u> Feet	<u>695</u> Feet
<u>12.25</u> Inches	<u>695</u> Feet	<u>1015</u> Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>14</u>	<u>54.5</u>	<u>0.375</u>	<u>0</u>	<u>31</u>
<u>8.625</u>	<u>22.4</u>	<u>0.250</u>	<u>0</u>	<u>1008.67</u>

Perforations:

Type perforation Louwer  
 Size perforation Full-Flow

From	To
<u>126</u> feet	<u>1008.67</u> feet

Surface Seal:  Yes  No  
 Depth of Seal Mined Off  
 Placement Method:  Pumped  Poured  
 Seal Type:  Neat Cement  Cement Grout  Concrete Grout

Gravel Packed:  Yes  No  
 From 0 feet to 810 feet

9. WATER LEVEL

Static water level 444 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor  
 Address P.O. Box 5279 Contractor  
Elko, NV 89802-5279  
 Nevada contractor's license number issued by the State Contractor's Board 0021976  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2039

Signed Dennis Robblee  
 By driller performing actual drilling on-site or contractor  
 Date 5/3/02

BST.C