CEX-6

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 97887
Permit No. 63070E
Basin 084

NOTICE OF INTENT NO. 43872

1. OWNER BOEING NORTH AMERICAN, INC.
MAILING ADDRESS 6633 Canoga Avenue
Canoga Park, California 91309

ADDRESS AT WELL LOCATION Rocketdyne
Former NFL-Area C
Whiskey Springs Road, Reno NV 89510

2. LOCATION NE ¼ SE ¼ Sec. 18 T. 22N N/S R. 22 E. Washoe County
PERMIT NO. ~~63071E~~ ~~CEX-6~~ 63070E Issued by Water Resources | 077-310-03 Parcel No. | Palomino Valley Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

*4. PROPOSED USE H2O Extrat.
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor* ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☒ Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Silty sand. Brown, fine grained sand with 30-40% silt, loose dry		0	15	14
Sand. Brown, coarse/med/fine grained sand, 20% silt, minor clay, 10% gravel		15	25	10
Increaseing gravel with depth, 20-30% gravel		25	48	23

Date Started July 18, 2000, 19
Date completed July 19, 2000, 19

RECEIVED JUL 15 2002 STATE ENGINEER'S OFFICE

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Not known			
Plugged by well log 116212			

8. WELL CONSTRUCTION
Depth Drilled 48 Feet Depth Cased 46 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	48 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	15
6 5/8X3/8" steel adaptor				
6" Stainless Steel screen/Welded stainless steel bottom cap 2'				

Perforations:
Type perforation factory sawed slot
Size perforation 0.200
From 15 feet to 45 feet
From feet to feet
From Surface completion 0 to 4 feet feet
From 0 to 4 ft. 4x4x4 open bottom concrete
From vault with metal lid

Surface Seal: ☒ Yes ☐ No
Depth of Seal 6 feet/4 ft.-10 ft.
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Bentonite Seal: 10-12 feet
Gravel Packed: ☒ Yes ☐ No #30 Sand 12-13 ft.
From 13-46 ft #8 Sand/46-48 ft. gravel feet

9. WATER LEVEL
Static water level 22 feet below land surface
Artesian flow not known G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. Contractor
Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908/923
Signed [signature] By driller performing actual drilling on site or contractor
Date June 23, 2002

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627