WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 87475
Permit No. 26388
Basin 069

NOTICE OF INTENT NO. 045238

1. OWNER Dave Rowe
MAILING ADDRESS 5900 Feedlot Rd.
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION Feedlot Rd

2. LOCATION SE 1/4 NE 1/4 Sec. 36 T 38N N/S R 38E E Humboldt County
PERMIT NO. 26388 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☒ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
ABANDONMENT				
Perforated well		0	40	40
Perforated well		65	110	45
Ran trimmie pipe down well and pumped 20,952 lbs. of cement and 800 lbs. of bentonite from the bottom of well to the top.		0	110	110

Date started 7/6/01, 19__
Date completed 2/8/02, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 240 Feet Depth Cased 240 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
16 Inches	0 Feet	240 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16				

Perforations:
Type perforation mill knife cuts
Size perforation 1/4 x 3
From 40 feet to 65 feet
From 110 feet to 147 feet
From 165 feet to 209 feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal 110
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 55 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed [signature] (By driller performing actual drilling on-site or contractor)

Date 2/22/02

HUMBOLDT DRILLING & PUMP CO., INC.
4675 W. Winnemucca Blvd.
Winnemucca, NV 89445
Phone: 775-623-5259 Fax: 775-623-0307

Well Log # 87975
Permit 26388

[redacted]

April 1, 2002

[redacted]

Tim Hunt
Division of Water Resources
123 W. Nye
Reno, NV 89710

RE: David Rowe
Permit #26388 Abandoning Well

In this particular area, water is very aggressive to steel. We drilled a small 6" domestic well and it lasted only a few years. Before PVC was allowed in Nevada, we asked and received a waiver to install PVC casing in the next well we drilled for Dave Rowe. The 16" casing had failed before PVC casing was allowed. We tried to bail this well out and we would bail the sand without making any headway. The scow was not advancing any deeper, so we perforated the casing that was there and set trimmie pipe and pumped neat cement.

Thank you very much.

Sincerely,

Gary D. Tompkins