WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 888174
Permit No.
Basin 087

NOTICE OF INTENT NO. 50514

1. OWNER Keith Bartelheim
MAILING ADDRESS 3675 Baker Ln
Reno NV 89509

ADDRESS AT WELL LOCATION 3675 Baker Ln
Reno NV 89509

2. LOCATION NW ¼ NE ¼ Sec. 25 T. 19N N/S R. 19 E. Washoe County
PERMIT NO. (Issued by Water Resources) 024032/12 (Parcel No.) Moana Park Home Sites (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Well was adandoned on April 3/2003 Attempts to pull well casing failed casing ripped in half approximately 3 feet from the surface at that time it was determined that the well was constructed out of black iron threaded and coupled pipe. Attempts to perforate pipe failed because inside diameter was too small for the perforatie. At this time we were instructed by Tim Hunt to install trimmy pipe and grout the well. there was approximately 4 feet of standing water in the bottom of the 42 ft wellat time of grouting				

Date started April 3/2003, 19
Date completed April 3/2003, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 42ft Feet Depth Cased 42ft Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
Type perforation
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 38 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Knoblock & Sons Pump and Supply (Contractor)
Address 5425 Spanish Moss (Contractor)
Sparks NV 89436

Nevada contractor's license number issued by the State Contractor's Board 49162

Nevada driller's license number issued by the Division of Water Resources, the on-site driller AB2213

Signed [signature] (By driller performing actual drilling on site or contractor)
Date April 4/2003

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627