

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. **50830**

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

1. OWNER Barrick Goldstrike Mines VD97-18 ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV.  
 MAILING ADDRESS P.O. Box 29  
Elko, NV 89822

2. LOCATION NW 1/4 NE 1/4 Sec. 19 T 36N N/S R 50E E Eureka County  
 PERMIT NO. 55141 Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE 10 mms/Anfing  
 Domestic  Irrigation  Test  Cable  Rotary  RVC  
 Municipal/Industrial  Monitor  Stock  Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

| Material  | Water Strata | From | To | Thick-ness |
|---|--------------|------|----|------------|
| Abandoned by pumping abantonite from T.D. to 241', then poured hole plug and abantonite to 20' and capped with neat cement. |              |      |    |            |
| Quantities Used:  |              |      |    |            |
| Cement: 5.9 cu.ft.  |              |      |    |            |
| Hole plug: 45 cu.ft.  |              |      |    |            |
| Abantonite: 187.1 cu.ft.  |              |      |    |            |

8. WELL CONSTRUCTION

Depth Drilled 850 Feet Depth Cased 840 Feet

HOLE DIAMETER (BIT SIZE)

|              | From    | To       |
|--------------|---------|----------|
| 17.5 Inches  | 0 Feet  | 20 Feet  |
| 9.625 Inches | 20 Feet | 850 Feet |
| Inches       | Feet    | Feet     |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 12.75              | 33.38               | 0.250                   | 0           | 20        |
| 6.625              | 17.02               | 0.250                   | +1.5        | 840       |

Perforations:  
 Type perforation Louver  
 Size perforation 0.125"

| From       | To         |
|------------|------------|
| 120 feet   | 840 feet   |
| _____ feet | _____ feet |
| _____ feet | _____ feet |
| _____ feet | _____ feet |
| _____ feet | _____ feet |

Surface Seal:  Yes  No  
 Depth of Seal 100'  
 Placement Method:  Pumped  Poured  
 Seal Type:  Neat Cement  Cement Grout  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 100 feet to 850 feet

9. WATER LEVEL  
 Static water level: 463 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Lang Exploratory Drilling Contractor  
 Address P.O. Box 5279 Contractor  
Elko, NV 89802-5279  
 Nevada contractor's license number issued by the State Contractor's Board 0021976  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1716  
 Signed Dave Haas  
 By driller performing actual drilling on-site or contractor  
 Date 1/17/03

Date started 1/12/2003, 19  
 Date completed 1/13/2003, 19

7. WELL TEST DATA

| TEST METHOD: | <input type="checkbox"/> Bailer | <input type="checkbox"/> Pump | <input type="checkbox"/> Air Lift |
|--------------|---------------------------------|-------------------------------|-----------------------------------|
| G.P.M.       | Draw Down (Feet Below Static)   | Time (Hours)                  |                                   |
|              |                                 |                               |                                   |
|              |                                 |                               |                                   |

RECEIVED  
 03 JAN 24 AM 11:16  
 STATE ENGINEERS OFFICE

*Drilled under proposed use  
 K*