Heap leach well

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 89113
Permit No.
Basin 0666

NOTICE OF INTENT NO. 74410

1. OWNER Getchell Gold Corp
MAILING ADDRESS P.O Box 220 Golconda, Nv. 89414
ADDRESS AT WELL LOCATION Mine Site North of Golconda

2. LOCATION SE ¼ SE ¼ Sec. 3 T. 38 N/S R. 42 E. Humboldt County
PERMIT NO. N/A Issued by Water Resources | N/A Parcel No. | N/A Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvial Gravel		0	62	
Sand & Gravel		62	82	
Larger Gravel Sand		82	105	
Sand Gravel & Clay		105	200	
hard Black Rock		200	210	
Fractured Rock		210	228	
hard Black Rock		228	231	
Fracture Rock Some Clay		231	243	
hard Black Rock		243	251	
Fractures		251	256	
hard Rock		256	257	
Fractures	XX	257	260	
hard Rock		260	262	
Fractures More H2O	XX	262	284	
hard Rock		284	286	
Fractures with Clay		286	298	
hard Rock		298	302	
Fractures		302	305	
Cement		25	0	
Abantonite		222	25	
Hole Plug		232	222	
#8 Sand		297	232	

Date started 12-13 2002
Date completed 12-18 2002

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☒ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
SQUIDE	Would NOT Pump		
	8	UNKNOWN	28.5 hrs

8. WELL CONSTRUCTION
Depth Drilled 305 Feet Depth Cased 297' Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 5/8 Inches		0 Feet	20 Feet
8 1/4 Inches		20 Feet	305 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"		.250	+2	297

Perforations:
Type perforation Screen PVC
Size perforation .020
From 237 feet to 297 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 222'
Placement Method: ☒ Pumped - Cement ☒ Poured - Bentonite
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 232 feet to 297 feet

9. WATER LEVEL
Static water level 241 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature Cool °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Fred Anderson Drilling Contractor
Address 10760 Grass Valley Road Contractor
Winn, Nv 89445
Nevada contractor's license number issued by the State Contractor's Board 021467
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 01375
Signed [signature] By driller performing actual drilling on site or contractor
Date 12-30-02

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627