WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 89314
Permit No.
Basin 085

NOTICE OF INTENT NO. 47714

1. OWNER BRADLEY SWITZER
MAILING ADDRESS 7112 Heartland Way
San Jose, California 95135

ADDRESS AT WELL LOCATION 3105 Barranca Drive
Sparks, Nevada 89436

2. LOCATION SE ¼ SE ¼ Sec. 7 T 21N N/S R 21 E Washoe County
PERMIT NO. (Issued by Water Resources) 076-290-22 (Parcel No.) Spanish Springs (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Decomposed granite		1	3	2
Weathered granite		3	235	232
Gray hard granite		235	305	70
Weathered granite, some clay streaks		305	402	97
Gray granite		402	798	396
Gray granite with some weathered streaks		798	967	169
Fracture (app 3 GPM)	X	967	968	1
Gray granite, some fracture (NO WATER)		968	1107	139
Fracture	X	1107	1109	2
Gray & weathered granite		1109	1129	20
Fracture	X	1129	1134	5
Weathered granite		1134	1140	6

Date started May 23, 2002, 19
Date completed June 7, 2002, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
10+		

8. WELL CONSTRUCTION
Depth Drilled 1140 Feet Depth Cased 1140 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches	0 Feet	50 Feet
8 5/8 Inches	50 Feet	1140 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	1171
5" OD		.188	1161	1140

NOTE: Liner has bottom cap with 1¼" dia. hole in center.

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 1011 feet to 1171 feet 6 5/8"
From 1161 feet to 1140 feet 5"
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 1140 feet

9. WATER LEVEL
Static water level 935 feet below land surface
~~Artesian flow~~ ~~10+~~ G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed [signature] (By driller performing actual drilling on site or contractor)
Date June 11, 2002

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627