

OFFICE USE ONLY
 Log No. 90834
 Permit No.
 Basin. 092B

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT
 Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 48436

1. OWNER ANDREW WILLIAMS & RUTH LENZ ADDRESS AT WELL LOCATION Same
 MAILING ADDRESS 10565 Deodar Way
Reno, Nevada 89506
 2. LOCATION SW 1/4 SE 1/4 Sec. 26 T 21N N/S R 19 E Washoe County
 PERMIT NO. 080-285-07 Lemmon Valley
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other.....

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
WELL DEEPENING				
8" dia well				
Static Water Level @99.7 feet				
Total depth @119 feet				
Total depth @120 feet at bottom of 8 5/8" casing				
Cement seal located with Down Hole Perforator @20 ft. cut 3 test holes @12,000 PSI to penetrate				
@25 ft. cut 3 test holes @12,000 PSI to penetrate				
@28 ft. refusal @20,000 PSI				
@30 ft. refusal @20,000 PSI +				
Perforate existing 8" dia steel casing from 7 to 28 ft.				
Soft brown clays		120	145	25
Weathered granite with clay streaks		145	183	38
Weathered granite		183	186	3
Weathered gray granite		186	221	35
Fracture granite	X	221	264	43
Weathered granite		264	267	3
Fracture granite	X	267	288	21

8. WELL CONSTRUCTION
 Depth Drilled 288 Feet Depth Cased 288 Feet
 HOLE DIAMETER (BIT SIZE)
 From 8 Inches To 120 Feet 288 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	288

Perforations:
 Type perforation factory sawed slot
 Size perforation 3/32 x 3 x 5 around
 From 224 feet to 284 feet
 _____ feet to _____ feet
 Surface Seal: Yes No Seal Type:
 Depth of Seal 7 to 47 feet between Neat Cement
8 5/8 & 6 5/8 casings Cement Grout
 Placement Method: Pumped Poured Concrete Grout
 Gravel Packed: Yes No
 From 47 feet to 288 feet

9. WATER LEVEL
 Static water level 108 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
 Nevada contractor's license number issued by the State Contractor's Board 0022549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date September 24, 2003

Date started September 15, 2003, 19____
 Date completed September 17, 2003, 19____

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>30+</u>		