WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 92107
Permit No.
Basin 094

NOTICE OF INTENT NO. 48444

1. OWNER DARRYL & VALORIE BUSH
MAILING ADDRESS 2970 Hawk Street, Carson City, Nevada 89704
ADDRESS AT WELL LOCATION 400 Desert Sun Lane, Reno, Nevada 89506

2. LOCATION NE ¼ NE ¼ Sec. 7 T. 22N N/S R. 19 E. Washoe County
PERMIT NO. (Issued by Water Resources) 079-382-46 (Parcel No) Red Rock Estates, lot 89, par. 4 (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Brown sandy clays		1	12	11
Decomposed sands		12	14	2
Brown sandy clays		14	46	32
Soft zone		46	48	2
Brown sandy clays		48	79	31
Brown sand		79	80	1
Brown sandy clays		80	161	81
Green sandy clays		161	170	9
Soft zone	X	170	173	3
Green sandy clays		173	197	24
Soft zone	X	197	210	13
Green sandy clays		210	235	25
Soft zone	X	235	239	4
Green sandy clays		239	248	9

Date started 11-3-03, 19
Date completed 11-5-03, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
15		

8. WELL CONSTRUCTION
Depth Drilled 248 Feet Depth Cased 248 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	248 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	248

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 201 feet to 241 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50 feet
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 248 feet

9. WATER LEVEL
Static water level 78 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed [signature] (By driller performing actual drilling on site or contractor)
Date November 10, 2003

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O) 627