ENTERED ON COMPUTER dh

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

OFFICE USE ONLY
Log No. 92779
Permit No.
Basin

WELL DRILLER'S REPORT

Please complete this form in its entirety

PRINT OR TYPE ONLY

NOTICE OF INTENT NO. 9955

1. OWNER City of Winnemucca
MAILING ADDRESS Winnemucca, NV 89445

ADDRESS AT WELL LOCATION

2. LOCATION NE ¼ SE ¼ Sec. 29 T. 36 N/S R. 38 E. Humboldt County
PERMIT NO. (Issued by Water Resources) Parcel No. Subdivision Name

3. TYPE OF WORK
New Well ☒ Recondition ☐
Deepen ☐ Other ☐

4. PROPOSED USE
Domestic ☒ Irrigation ☐ Test ☐
Municipal ☐ Industrial ☐ Stock ☐

5. TYPE WELL
Cable ☐ Rotary ☒
Other ☐

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Boulders w/5% Clay		0	170	170
Sand & Gravel w/s boulders & 5% Clay		170	190	20
Sand & gravel w/5% clay		190	295	105
60% clay w/s sand & gravel		295	300	5
Sand and gravel		300	305	5
Sand and gravel w/10% clay		305	309	4
Sand and gravel w/2% clay		309	312	3
Sand and gravel w/10% clay		312	385	73
Sand and gravel w/2% clay		385	395	10
Sand and gravel w/10% clay		395	430	35
Sand and gravel w/5% clay		430	438	8
Sand and gravel w/5% clay		438	515	77
70% Clay w/s sand		515	565	50
Clay		565	570	5
70% Clay w/s sand		570	580	10
90% clay w/s sand		580	585	5
70% clay w/s sand		585	587	2
90% clay w/s sand		587	605	18

RECEIVED
OCT 27 PM 12 07
STATE ENGINEERS OFFICE

Date started 7/11, 1988
Date completed 8/5, 1988

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
	2800	265'	40

BAILER TEST
G.P.M. Draw down feet hours
G.P.M. Draw down feet hours
G.P.M. Draw down feet hours

8. WELL CONSTRUCTION
Diameter 24" inches Total depth 605 feet
inches
inches
Casing record 16"
Weight per foot Thickness ¼
0-10 3" Conductor Cemented in
+1-63 20" Conductor Cemented in

Diameter	From	To
16" Blank inches	43 feet	227 feet
16" Perf inches	227 feet	347 feet
16" FF inches	347 feet	362 feet
16" Perf inches	362 feet	382 feet
16" FF inches	382 feet	402 feet
16" Perf inches	402 feet	462 feet

Surface seal: Yes ☒ No ☐ Type Concrete
Depth of seal 60' feet
Gravel packed: Yes ☒ No ☐
Gravel packed from 0 feet to 605 feet

Perforations:
Type perforation
Size perforation
From 16" Perf 482 feet to 577 feet
From 16" Blank 577 feet to 602 feet
From Concrete Plug 602 feet to 605 feet
From feet to feet
From feet to feet

9. WATER LEVEL
Static water level 126' feet below land surface
Flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Umca Blvd. Winnemucca, NV 89445 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada contractor's driller's number issued by the Division of Water Resources C-23
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1490
Signed [signature]
By driller performing actual drilling on site or contractor
Date 8-23-88

(Rev. 11-85) USE ADDITIONAL SHEETS IF NECESSARY (O)-627