WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 93640
Permit No.
Basin 7

NOTICE OF INTENT NO. 51946

1. OWNER Carlos Ceballos
MAILING ADDRESS 17000 Grass Valley Rd
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION same

2. LOCATION NW 1/4 SW 1/4 Sec. 29 T 34N N/S R 38E E Pershing County
PERMIT NO. 70996T & 70995T (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [X] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy clay		0	10	
sand & gravel		10	35	25
sand & gravel w/cobbles		35	510	475

04 APR 26 P1:41
STATE ENGINEER'S OFFICE

Date started 4/12/04, 19__
Date completed 4/15/04, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [X] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
P/L 195	3000	71	7 hrs

8. WELL CONSTRUCTION
Depth Drilled 510 Feet Depth Cased 500 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
36 Inches		0 Feet	50 Feet
24 Inches		50 Feet	510 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
30		culvert	0	50
16		.250	+1	100

Perforations:
Type perforation mill slot
Size perforation .090
From 100 feet to 180 Double Row feet
From 180 feet to 220 quad feet
From 220 feet to 260 double row feet
From 260 feet to 340 quad feet
From 340 feet to 500 double row feet

MD 8/31

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 3 feet to 510 feet

9. WATER LEVEL
Static water level 124 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445

Nevada contractor's license number issued by the State Contractor's Board 56797

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed [signature] (By driller performing actual drilling on-site or contractor)

Date 4/23/04