STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 95904
Permit No. 108
Basin

NOTICE OF INTENT NO. 54688

1. OWNER MIKE FARETTO
MAILING ADDRESS 291 OSBORNE LANE
YERINGTON, NV 89447

ADDRESS AT WELL LOCATION
HWY 208 MASON VALLEY

2. LOCATION 1/4 SW 1/4 Sec 14 T 12 N/S R 25 E LYON County
PERMIT NO. W581/72131
Issued By Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [X] Test
[ ] Municipal/Indu [ ] Monitor [ ] Shock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other MUD

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOP SOIL		0	5	5
SAND AND GRAVEL		5	100	95
BROWN CLAY		100	130	30
BOULDERS		130	150	20
SAND AND GRAVEL		150	160	10
CLAY		160	180	20
SANDY CLAY		180	220	40
CLAY		220	260	40
SANDY CLAY		260	280	20
CLAY		280	300	20
SAND		300	320	20
BROWN CLAY		320	540	220
GREEN CLAY		540	600	60
0 TO 10 FEET--NEAT CEMENT SEAL				
10 TO 600 FEET--HOLE PLUG				
60 sacks whole plug				

RECEIVED 05 MAR -7 PM 1:12 STATE ENGINEER'S OFFICE

Date Started FEBRUARY 17 2005
Date Completed FEBRUARY 18 2005

7. WELL TEST DATA
TEST METHOD:
[ ] BAILER [ ] PUMP [ ] AIR LIFT

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA			

8. WELL CONSTRUCTION
Depth Drilled 600 Feet Depth Cased NA Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6 1/2	Inches	0	Feet	600	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (inches)	Weight (pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
		NA		

Perforations:
Type Perforation NA
Size Perforation
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 10'
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout
Placement Method: [ ] Pumped [X] Poured
Gravel Packed: [ ] Yes [ ] No
From feet to feet
From feet to feet

9. WATER LEVEL
Static Water Level 20 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 70 °F Quality FAIR

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Hydro Resources Nevada Inc. dba Humboldt Drilling and Pump Co.
Address 4975 West Winnemucca Boulevard
Winnemucca, Nevada 89445
Nevada Contractor's license number issued by the State Contractor's Board 56797
Nevada Driller's license number issued by the Division of Water Resources, the on-site driller 2099
Signed: Jim Shaw Date: 2/24/05