WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 96226
Permit No.
Basin 203

NOTICE OF INTENT NO. 79487

1. OWNER Unknown "Farm well"
MAILING ADDRESS D.O.T.
ADDRESS AT WELL LOCATION 3 Miles out 9 mile East on Highway 319 Panaca NV

2. LOCATION SW ¼ NW ¼ Sec. 8 T. 2 N/S R. 68 E. Lincoln County
PERMIT NO. — Issued by Water Resources; Parcel No.; Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
This was a farm well casing used was 8" column pipe, I was broke off 3' under ground at a threaded joint. Rethreaded broken section drilled out well from 84' to 98' which I believe was hard bottom. Perforated using mills knife from 3' to 98'. Installed 3" tremmie pipe cemented to surface. Pulled top 3' section out of hole. During this time cement fell approx 30'. Filled hole again to surface with neat cement. Hole used approx 340 gals water and 680 Lbs cement				

UNKNOWN RECEIVED MAY 02 2005 LAS VEGAS OFFICE

Date started 4-27-05, 19
Date completed 4-28-05, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled ____ Feet Depth Cased ____ Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8"		1/4"	0	98

Perforations:
Type perforation 5/16 x 2"
Size perforation mills knife
From 0 feet to 98 feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal 98
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From ____ feet to ____ feet

9. WATER LEVEL
Static water level 29 feet below land surface
Artesian flow ____ G.P.M. ____ P.S.I.
Water temperature ____ °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Davis Drilling and Pumps (Contractor)
Address HC61 Box 54 Hiko NV 89017 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 0028866
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 7181
Signed Mike Davis (By driller performing actual drilling on site or contractor)
Date 4-28-05

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627