WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 97101
Permit No.
Basin 003

NOTICE OF INTENT NO. 56280

1. OWNER R.D.D. Inc.
MAILING ADDRESS 290 East Minor Street Winnemucca Nv. 89445
ADDRESS AT WELL LOCATION Knott Creek Ranch

2. LOCATION NE ¼ SW ¼ Sec. 3 T. 43 N/S R. 27 E. Humbolt County
PERMIT NO. 65568-65569 (Issued by Water Resources) 62-341-02 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SAND-GRAVEL-COBBLES		0	22	
CLAY		22	30	
COBBLES-SAND-CLAY		30	105	
RED CLAY-SAND		105	128	
COARSE SAND W/CLAY		128	195	
HARD BRN CLAY		195	225	
SAND-GRAVEL-CLAY		225	275	
SOFT BRN CLAY-SAND		275	345	
SAND & GRAVEL-CLAY		345	375	
SAND & CLAY		375	430	
SAND & GRAVEL-CLAY		430	500	
CLAY-SAND		500	540	
SAND & GRAVEL		540	560	
SAND & CLAY STRATAS		560	610	
CLAY W/SAND		610	670	
SAND W/CLAY STRATAS		670	710	
CLAY		710	750	
SAND & GRAVEL W/CLAY		750	780	
CLAY		780	830	
SAND & GRAVEL		830	955	
SAND & GRAVEL W/CLAY		955	995	
SAND & GRAVEL		995	1015	

Date started 5-3-05, 19
Date completed 5-6-05, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1,015 Feet Depth Cased 1,000 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
36" Inches	0 Feet	50 Feet
28" Inches	50 Feet	1015 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16"		1/4"	+2	1,000

Perforations:
Type perforation Double Row Mill Slot
Size perforation 1/4 Inch
From 60 feet to 1,000 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level 89 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name ANIS Enterprises (Contractor)
Address 399 Denio Hy 140 (Contractor)
Winnemucca Nv. 89445
Nevada contractor's license number issued by the State Contractor's Board 0058683
Nevada driller's license number issued by the Division of Water Resources, the on-site driller
Signed Ralph C. Schoch (By driller performing actual drilling on site or contractor)
Date 6-13-05

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627