WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1
Rec. Feb. 14 1950
Well No.
Permit No.
Do not fill in

Owner Riverside Hotel Driller Lee Smith

Address Reno Address Reno Lic. No. 29

Location of well: ¼ ¼ Sec. 11, T. 19 N/S, R. 19 E, in Washoe County

or

Water will be used for Air Conditioning Total depth of well 360'

Size of drilled hole 14" Weight of casing per linear foot

Thickness of casing Temp. of water 56

Diameter and length of casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 18'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well May 9-1949 Date of completion of well July 1 - 1949

Type of well rig Bucyrus Eire 24L Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	7	7	Boulders & Clay
7	11	4	" " "
11	26	15	" "
26	33	7	" " "
33	39	6	Boulders & Sand - W
39	42	3	" " " W
42	50	8	Gravel & clay
50	62	12	Gravel & Clay
62	80	18	Large gravel & clay
80	102	22	" " " "
102	107	5	" " " "
107	123	16	Brown Clay
123	124	1	" "
124	131	7	Gravel Sand & water
131	133	2	Brown Clay
133	159	26	" "
157	165	8	Gravel Sand & clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 336 to 356 ft.

Other aquifers 217' - 230'
Gravel & SAND
124 - 131
Gravel SAND WATER

First water at 39 feet.

Casing perforated

from 124 to 131 - 336 to 356 ft.

Size of perforations

3 X 1/4

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
165	171	6	Gravel sand & clay
171	180	9	Clay
180	186	6	Gravel & clay
186	212	[illegible]	" "
212	217	5	Gravel & sand some water
217	230	13	Sand & clay
230	240	10	Gravel & clay
240	256	16	" "
256	268	12	" "
268	329	61	Large gravel & clay
329	336	9	Brown clay
336	338	2	Large gravel sand W
338	350	12	" " " " "
350	356	6	" " " " "

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
356	360	4		Grey clay

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed John Thompson
Well Driller

By.....

License No. 29

Dated....., 194.....

(Not to be filled in by Driller)