WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 99533
Permit No.
Basin 092B

NOTICE OF INTENT NO. 56360

1. OWNER Liina R Mandik
MAILING ADDRESS 625 Oregon Reno NV 89506
ADDRESS AT WELL LOCATION 625 Oregon

2. LOCATION NW ¼ NW ¼ Sec. 15 T. 21 N/S R. 19 E. Washoe County
PERMIT NO. (Issued by Water Resources) 08040402 (Parcel No.) Lemmon Valley (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☑ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☑ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Well was abandoned				
1/26/2006				
Attempts to pull well				
casing failed				
well was perforated				
from 200 ft to 50ft				
A 6 inch mills knife				
wass used to perforat				
the well.				
4 perforation per ft				
A 2 inch pipe wasset				
set to 278 ft and				
Neat cement was pump				
to top of well.				

Date started 1/26/2006, 19
Date completed 1/26/2006, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 278 Feet Depth Cased 278 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.5	188	0	200
5		188	200	278

Perforations:
Type perforation Factory
Size perforation 1/16
From 180 feet to 278 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 50 ft
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level 260 feet below land surface
Artesian flow 0 G.P.M. 0 P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) Knoblock & Sons Pump and Supply
Address (Contractor) 5425 Spanish Moss
Sparks NV 89436
Nevada contractor's license number issued by the State Contractor's Board 49162
Nevada driller's license number issued by the Division of Water Resources, the on-site driller AB3213
Signed (By driller performing actual drilling on site or contractor)
Date 1/26/2006

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 3-91) (O)-627