

COPIES TO  
 - DIVISION OF WATER RESOURCES  
 - CLIENT'S COPY  
 - WELL DRILLER'S COPY

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
 Log No. 99605  
 Permit No. \_\_\_\_\_  
 Basin 101  
 NOTICE OF INTENT NO. 56669

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER **CASEY PROPERTIES**  
 MAILING ADDRESS 4240 RENO HWY  
FALLON, NV 89406  
 ADDRESS AT WELL LOCATION  
1703 ROBERSON  
FALLON, NV 89406

2. LOCATION NW 1/4 NW 1/4 Sec 19 T 19 N R 28 E CHURCHILL County  
 PERMIT NO. SE NE 008-133-42

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

| Material    | Water Strata | From | To  | Thick-ness |
|-------------|--------------|------|-----|------------|
| TOP SOIL    |              | 0    | 1   | 1          |
| BROWN SAND  |              | 1    | 10  | 9          |
| BROWN CLAY  |              | 10   | 13  | 3          |
| BROWN SAND  |              | 13   | 29  | 16         |
| BROWN CLAY  |              | 29   | 33  | 4          |
| GRAY SAND   |              | 33   | 65  | 32         |
| GRAY CLAY   |              | 65   | 74  | 9          |
| GRAY SAND   |              | 74   | 85  | 11         |
| GRAY CLAY   |              | 85   | 88  | 3          |
| BROWN SANDS | X            | 88   | 100 | 12         |

8. WELL CONSTRUCTION  
 Depth Drilled 100 Feet Depth Cased 100 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From To  
10 3/4 Inches 0 Feet 50 Feet  
6 Inches 50 Feet 100 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 CASING SCHEDULE  

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet)  |
|--------------------|---------------------|-------------------------|-------------|------------|
| <u>6 5/8</u>       | <u>12.9</u>         | <u>.188</u>             | <u>+2</u>   | <u>100</u> |

Perforations:  
 Type perforation MACHINE SLIT  
 Size perforation .088  
 From 92 feet to 96 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 50  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

9. WATER LEVEL  
 Static water level 12'4" feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature COOL °F Quality UNTESTED

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WELSCO CORP  
 (CONTRACTOR)

Address P. O. BOX 888  
 (CONTRACTOR)  
FALLON, NV 89406  
 Nevada contractor's license number issued by the State Contractor's Board 11752  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2199  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date APRIL 10, 2006

Date started MARCH 23, 20 06  
 Date completed MARCH 23, 20 06

7. WELL TEST DATE

| TEST METHOD: | Bailer                        | Pump                     | Air Lift                            |
|--------------|-------------------------------|--------------------------|-------------------------------------|
| G.P.M.       | <input type="checkbox"/>      | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| Time (Hours) | Draw Down (Feet Below Static) |                          |                                     |
| <u>20</u>    | <u>1 HR</u>                   |                          |                                     |