WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 99927
Permit No.
Basin 029

NOTICE OF INTENT NO. 56091

1. OWNER High Desert Ranch
MAILING ADDRESS 396 Denio Hy 140
Winnemucca NV 89445

ADDRESS AT WELL LOCATION

2. LOCATION NW ¼ SW ¼ Sec. 22 T. 44 N/S R. 31 E. Humbolt County
PERMIT NO. 50996 50997 / 73700-1 Apps to Change
Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☑ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☑ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☑ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
DG		0	60	
Sandy clay		60	70	
Sand / Gravel / Cobbles		70	95	
Sand / Gravel		95	130	
Clay / DG		130	140	
Sand		140	150	
DG		150	160	
DG / Soft brn clay		160	180	
DG		180	220	
DG / Clay		220	280	
Clay / DG stringers		280	300	
DG / Clay		300	360	
Clay / DG		360	420	
DG / Clay		420	440	
Clay / DG		440	490	
Brn Clay		490	540	
DG / gravel		540	570	
Brn Clay / DG		570	600	
DG - Sand		600	610	
Clay		610	620	
Sand / Gravel		620	630	
Clay		630	640	
Sand Gravel		640	650	
Clay		650	660	
Sand / Gravel		660	670	
Clay		670	700	
Small Gravel		700	710	
Clay		710	720	
Sand / Gravel / Cobbles		720	800	

Date started 3-13, 2006
Date completed 3-18, 2006

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 800 Feet Depth Cased 800 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
28	0	800

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		1/4"	+1	800

Perforations:
Type perforation Double Row Mill slot
Size perforation 1/4"
From 120 feet to 800 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 0 feet to 800 feet

9. WATER LEVEL
Static water level 120 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name A N S Enterprises (Contractor)
Address 399 Denio Hy 140 (Contractor)
Winnemucca NV 89445
Nevada contractor's license number issued by the State Contractor's Board 58683
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2140
Signed Ralph Schrade (By driller performing actual drilling on site or contractor)
Date 5-12-06

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627